



Component - Plastics

File Number: E162823

FORMOSA CHEMICALS & FIBRE CORP PLASTICS DIV

201 TUNG HWA N RD
TAIPEI, 105 Taiwan

TAIRILITE: AC3900

Polycarbonate (PC), pellets



Flammability	Value	Test Method
Flame Rating		UL 94
1.5 mm, NC	V-0	IEC 60695-11-10, -20
3.0 mm, NC	V-0	
Electrical	Value	Test Method
Hot-wire Ignition (HWI)		UL 746
1.5 mm	PLC 3	
3.0 mm	PLC 2	
High Amp Arc Ignition (HAI)		UL 746
1.5 mm	PLC 1	
3.0 mm	PLC 0	
Comparative Tracking Index (CTI)	PLC 0	UL 746
High Voltage Arc Tracking Rate (HVTR)	PLC 3	UL 746
Arc Resistance	PLC 6	ASTM D495
Thermal	Value	Test Method
RTI Elec		UL 746
1.5 mm	80.0 °C	
3.0 mm	80.0 °C	
RTI Imp		UL 746
1.5 mm	80.0 °C	
3.0 mm	80.0 °C	
RTI Str		UL 746
1.5 mm	80.0 °C	
3.0 mm	80.0 °C	